

SWING GATE OPENER

SWARM600











GATEWAY TO CONVENIENCE AND SAFETY !!!





TECHNICAL CHARACTERISTICS









Motor

Gear type

Max. absorbed power

Peak thrust

Max. operating current

Nominal thrust

Max. gate weight

Max. gate length

24V DC

Worm gear

144 W

3500 N


5.5 A for maximum 10 sec

3500 N

300 kg per leaf

3 metres

DIMENSIONS








INTELLIGENT FEATURES

- The double gate opening system is a robust, tuff, long lasting and a quite opening and closing system for double swing gates upto 4 mtr in length.
- Applicable for residential and commercial purpose.
- Remote range is upto 50 Meters from the gate.
- Motor is designed as an Articulated motor with high pressure casting Body with fibre housing.
- Slow down its operation during the opening and closing phase.
- Worm gear provides durability and silence in motor operation.
- The motor is fitted with an emergency manual override on each motor to allow the user to open the gates manually in case of an emergency such as a power failure situation.
- The motor can handle both light and heavy gates.
- The two motors make up a durable and powerful DC unit and the gear box is heavy duty and all years are constructed of metal (no plastic, fibre or nylon)
- Can add any optional devices.
- The motor kit provides complete accessories and materials for easy installation.





WIRING DIAGRAM



- 1: Power Cable [P N E] (Guage depends on distance)
- 2: 2 core 1 sq cable 1st motor
- 3: 2 core 1 sq cable 2nd motor
- 4: Cat6 Cable- safety sensor
- 5: Cat6 Cable- safety sensor
- 6: 2 core 1 sq cable- lock 7: Cat6 cable- Flash light

OPTIONAL DEVICES



WIFI MODULE



PHOTOCELL



GSM



LOOP DETECTOR





UHF READER





SAFETY MATTERS

www.siwstech.com